

H23 Connecting Rods Main Sizes

Brand: Hurricane*	
Center to Center Length: 141.50mm/5.571"	
Big End Bore Diameter: 51.01mm/2.008"	
Big End Width: 23.75mm/0.935"	
Small End Bore Diameter: 22.01mm /0.867"	
Small End Width: 23.75mm/0.935"	
Beam Style: X-beam	

Honda/Acura H23/F22 Connecting Rods More Details

Connecting Rod Bolt Diameter	3/8 "
Approximate Connecting Rod Weight	~
Advertised Horsepower Rating	700hp
Package	4 pieces per set
Material	Forged 4340 steel
Connecting Rod Finish	Shot-peened, Polished
Pin	Bronze wrist pin bushings
Wrist Pin Style	Floating
Cap Retention Style	Cap screw
Weight Matched Set	Yes Balanced +/- 1g
Magnafluxed	Yes
Private Label	Yes, available
Custom design	Yes, accept

Honda Prelude Si H23 H23A Conrods Features

Hurricane H23 Connecting Rods are forged from SAE 4340 steel for superior strength. Hurricane replacement 3/8 bolts and alignment sleeves are used for durability and precise cap location. Honda Prelude Si H23 H23A Conrods are Shot Peened for improved fatigue life and balance weight matched to +/- 1g per set. X beam Connecting Rods Set for Honda Acura H23 /F22 2.2L 2.3L are the perfect choice for engines up to 700 horsepower.



Fitment:

Honda Prelude, Accord, Rover 1.4L I4

Honda H23 | Honda H23A | Honda F22 | Acura F22 | Acura H23

If you have any question about this product or need any further information, please feel free to [contact us](#). Our experianced sales staff is here to assist you any way they can.

1994 Honda Prelude Si Car



Note: Picture from Flickr.