

Evo X (4B11T) Connecting Rods Main Sizes

Brand: Hurricane	
Center to Center Length: 143.75mm/5.659"	
Big End Bore Diameter: 55mm/2.165"	
Big End Width: 21.87mm/0.861"	
Small End Bore Diameter: 23mm /0.906"	
Small End Width: 19.91mm/0.784"	
Beam Style: H-beam	

Mitsubishi EVO X 4B11T H Beam Connecting Rod Set Features

Connecting Rod Bolt Diameter	3/8 "
Approximate Connecting Rod Weight	550g
Advertised Horsepower Rating	550hp
Quantity	Sold as 4 pieces /set
Material	Forged 4340 steel
Connecting Rod Finish	Shot-peened, Polished
Pin	Bronze wrist pin bushings
Wrist Pin Style	Floating
Cap Retention Style	Cap screw
Weight Matched Set	Yes ,Balanced +/- 1g
Magnafluxed	Yes
Private Label	Yes ,available
Custom design	Yes, accept

Mitsubishi Lancer Evolution X 4B11T 4B11 connecting rods Description

Hurricane Mitsubishi Lancer Evolution X 4B11T 4B11 connecting rods are manufactured from 4340 forgings to hold massive amounts of power. Each rod is shot peened after machining and magnafluxed. Bores are

round and without taper. Bend and Twist is tightly controlled. Weight matched to +/- 1g. The H-beam connecting rod has become the industry standard design for high-performance applications. Considering the best overall performance of the part, combined with the least amount of weight, the H-beam is strongest, most durable design available. Hurricane H-Beam Evo X (4B11T) Connecting Rods are recommended for race applications. These H-Beam Forged Connecting Rods for the Evo X 4B11T come with 3/8th inch race spec rod bolts. Check more at: [Hurricane Connecting Rod Bolt Information](#)



For more compare pictures of our Mirco polished progress. Please check our [NEWS PAGE: *Connecting rods Shot Peening and Mirco-Polishing, Special A-level appearance*](#)

Hurricane Also offer custom design, if you do not find what you want from our website, You can fill in [Hurricane Speed & Performance - Custom Connecting Rod Form](#). Our skilled staff will contact and help you within 24 hours.

Here are some useful link about connecting rods designs:

- #1, [Hurricane Connecting Rods Big End Design](#)
- #2, [Hurricane Connecting Rod Shoulder Design](#)
- #3, [Hurricane Connecting Rod Features - Various Beam Designs](#)

Hurricane Speed & Performance is a Engine components factory in China. Performance connecting rods are our mature products. Here are some useful informations to know more about us:

Article : [Hurricane High Performance connecting rods - Process of machining rods](#)

Youtube Video: [How it's made: Connecting rod](#)

Youtube video: [Who we are - Hurricane Speed & Performance\(Connecting Rod\)](#)

H-Beam Forged Connecting Rods for the 4B11T FAQ

Q: What is the bolt torque required on rods?

A: Hurricane Race Spec ARP2000 5/16-1.500" 45N*m

Hurricane Race Spec ARP2000 3/8 -1.600" 75N*m

Hurricane Race Spec ARP2000 7/16-1.600" 95N*m

Q: Can I order a single connecting rod as sample to check quality first before cooperation?

A: Yes, Of course. Please [leave us message](#) with your requirements.

Q: What's your rods material and hardness?

A: Material: 4340 forged steel/40CrNiMoA/EN24. Heat Treatment: HRC34-38

Q: Could you provide logo printing(private label) service on connecting rods?

A: Yes.

Race Car Picture



