

Brand: Hurricane*
Engine: Suzuki swift M15A
Part Type: Connecting Rods
Center to Center Length: 138.00mm/5.433"
Big End Bore Diameter: 45.00mm/1.772"
Big End Width: 23.91mm/0.941"
Small End Bore Diameter: 20.01mm /0.788"
Small End Width: 18.90mm/0.744"
Beam Style: H-beam
Connecting Rod Bolt Diameter: 3/8"
Approximate Connecting Rod Weight: 525g/piece
Advertised Horsepower Rating: 600hp
Quantity: Sold as 4 pieces /set
Material: Forged 4340 steel
Connecting Rod Finish: Shot-peened, Polished
Pin: Bronze wrist pin bushings
Wrist Pin Style: Floating
Cap Retention Style: Cap screw
Weight Matched Set: Yes ,Balanced +/- 1g
Magnafluxed: Yes
Private Label: Yes ,available
Custom design: Yes, accept

These H Beam connecting rods designed and developed for Suzuki swift M15A engines , engineered from high tensile [4340 forged steel](#) material , high quality H-BEAM design for lighter weight, and all M15A rods are heat treated , magnafluxed, shot peened, fully machined in Hurricane factory for for superior fatigue life and high strength .



Per rod fully machine at [Hurricane CNC center](#) to handle maximum strength .



All big and small end bore honned with advanced honing machine for superior tight tolerance , per di mension inspected at workshop to guarantee high reliability .

In short, if you are looking for a strong rod for your racing Suzuki applications, Hurricane connecting rod will be a suitable one .