

Volvo 139.5mm Connecting Rods Main Sizes

Brand: Hurricane	
Center to Center Length: 139.5mm/5.492"	
Big End Bore Diameter: 53.00mm/2.087"	
Big End Width: 24.95mm/0.982"	
Small End Bore Diameter: 23mm /0.906"	
Small End Width: 25.65mm/1.010"	
Beam Style: H-beam	

Volvo 850 H-Beam Connecting Rods Features

Connecting Rod Bolt Diameter	3/8 "
Approximate Connecting Rod Weight	565 gram per piece
Advertised Horsepower Rating	750 HP
Quantity	Sold as 5 pieces per set
Material	Forged 4340 steel
Connecting Rod Finish	Shot-peened, Polished
Pin	Bronze wrist pin bushings
Wrist Pin Style	Floating
Cap Retention Style	Cap screw
Weight Matched Set	Yes Balanced +/- 1g per set
Magnafluxed	Yes
Private Label	Yes, available
Custom design	Yes, accept

H Beam Connecting Rods - Volvo B5 5 Cylinder 139.5mm Detailed Description

Hurricane H-Beam Forged Connecting Rod for 1998-2000 Volvo S70 2.3L B5234T3 I5 engine are produced from premium quality billet 4340 steel. Each rod is custom cast and core hardened for increased tensile strength. This process also helps reduce fatigue. Volvo 850 H-Beam Connecting Rods are honed-in house and held to right scope tolerances. Conrods For Volvo 850 C70 V70 T-5 2.3L 2.5L B5234T 139.5mm are

then weight-matched into sets and boxed for shipment.



Our volvo 139.5mm connecting rods are meant to replace your current factory connecting rods, this modification will allow you to run higher boost levels without the fear of bending a factory rod. H Beam Connecting Rods - Volvo B5 5 Cylinder 139.5mm suggest horsepower is 750HP.

VEHICLE FITMENT :

- 1994-1997 850 Turbo, T5, T5-R, R**
- 1998-2000 V70 GLT, T5, R**
- 1998-2000 S70 GLT, T5**
- 1998-2005 C70 LPT/HPT**

If you have any question, you can leave your message below or write email to [hurricane team](#).

Volvo 850 Engine



Note: Picture from Wikipedia Commons.